RFID-Based Equipment Monitoring System

Mohd Helmy Abd Wahab, Herdawatie Abdul Kadir, Zarina Tukiran, Nor'aisah Sudin, Mohd Hafiz A. Jalil and Ayob Johari Universiti Tun Hussein Onn Malaysia Malaysia

1. Introduction

Automated monitoring systems are becoming trends, creating easier method to identify item, tracking, monitoring and add on security values. In places where there are lots of items accessed by many users, the tendency of loss is high due to weakness in items monitoring. Here, we briefly describe our research on the university's laboratory perspectives. The main aim of the research is to work out a generic approach of monitoring items in a place with several rooms. For example, there are laboratories with expensive equipments are available in a university to support teaching and learning session. Conventional approach of checking items for every session is difficult for lab administrator as most libraries are being used by more than 20 students per session. These leads to a challenge for lab administrator to monitor the flow of these items are always in place. Currently, the monitoring of laboratory equipments is performed manually by the lab administrator during each laboratory sessions. For every loan of equipment, a log book needs to be filled up in order to keep track the transaction information. This system was found to have a lot of weaknesses such as misuse of the equipment log records, losses of equipment, no in-out transaction record and misplace of equipments. To automate the process, Radio Frequency Identification (RFID) is identified as one of the most practical and applicable in real time implementation in-line with the nature where most of the systems are made computerized. In this paper, a solution has been provided for the problem encountered in laboratory equipment monitoring system using RFID technology. Therefore RFID-based monitoring system has been designed and developed to solve the problem associated with the handling of laboratory equipments. This chapter is organised as follows. Section 2 describes related works on RFID-based monitoring system. The architecture of the system is mentioned in section 3. Application scenario and the implementation are briefly explained in section 4 and 5 respectively. Finally, the chapter is concluded in Chapter 6.

2. Related work on RFID in monitoring

RFID is a wireless automatic identification that is gaining attention and is considered by some to emerge as one of the pervasive computing technologies in history (Roberts, 2006). As the technology grows very rapidly, RFID has received considerable worldwide attention and widely used in monitoring and tracking ranging from human identification to product

identification. Previous research has successfully indicated that RFID has been increasingly expanded in various fields such as retail supply chain, asset tracking, postal and courier services, education, construction industry, medical, and etc.

The work presented by Tan and Chang (2010) who had developed an RFID-based erestaurant system to change the traditional restaurant services which is considered as passive. The utilization of RFID is to improve the service quality which is customer-centered that enable waiters to immediately identify customers via their own RFID-based membership card. It can also provide customized services such as enhanced dining table service; pay the bills, instant transmission of customer orders to kitchens and flexibility of managing payments of bills and discounts. However, in Ngai et. al. (2008), designed and developed RFID-based sushi management system to help a conveyor belt sushi restaurant to achieve better inventory control, responsive replenishment, and food safety control, as well as to improve its quality of service.

In the perspective of animal tracking or livestock monitoring management system, Vouldimos et al. (2010) developed FARMA project which combined with RFID technology and mobile wireless networking to track animal and the data in repository which contains animal data records. The purposes of the system are to identify animal in case it gets lost and identify some basic information about particular animals. A similar work done by Nor Suryani Bakeri et. al. (2007) and Ahmad Rafiq Adenan et. al. (2006) developed a livestock monitoring system using RFID. An RFID tag is used and attached to each livestock to monitor its movement in and out as well as the basic information about any particular animals.

The use of RFID also could assist in customs clearance process by reducing the delay time. According to Hsu, Shih and Wang (2009), the use of RFID can improve the efficiency of cargo process, and reduce the inventory and labor cost. The work presented based on the mathematical model of the customs clearance process-delay and the network of customs delay is reconstructed based on the use of RFID. RFID also has been successfully applied in global postal and courier services in monitoring the parcel delivery. One of the well known courier service company is DHL which has been using RFID in their services since 1988 and carried out 20 trials on active and passive technology and successfully proved it improved the service and reduce the costs (EPC Global, 2005). The application of RFID in global market in postal and courier services contribute 650 billion per year and Europe was the leader in utilizing RFID in postal and courier services (Zhang, et. al., 2006).

High quality service lead to customer satisfaction, increase market share, and enhance profitability of service organizations (Hoffman and Bateson, 1997). Oztaysi, Baysan, and Akpinar (2009) have done a study to investigate the possibility of using RFID as a tool for improving service quality in hospitality industry and primarily concern in tourism industry. In monitoring of asset tracking, an effective and efficient managing the tracking of medical-assets in healthcare facilities can be performed by the means of RFID. Oztekin et. al. (2010) has done a study using enhanced maximal covering location problem along with critical index analysis metric to optimize the design of a medical-asset tracking system constrained by a limited number of RFID readers. Results indicate that the proposed technique has improved by 72% compared to the currently utilized expert placement strategy.

Yan and Lee (2009) developed RFID application in Cold Chain monitoring system to track the cold-chain product flowing in supply chain, ensure the products' quality and comply with relevant provisions during transportation. The system executes in real-time environment and can track the location and monitor the temperature of cold-chain products to ensure the quality. However, according to Loebbecke (2005) has done a research regarding the application of RFID in retail supply chain at a brink-and-mortar supermarket to investigate the advantages and challenges with the early RFID applications in terms of technological issue such as standardization, challenges on the data, network and application layers.

Haron, et. al. (2010), designed and developed of a context aware notification system for university students using RFID. The system aims to deliver urgent notifications to the intended students immediately at their respective locations. A quite similar work done by Herdawatie et. al. (2010) which integrates RFID and biometric sensor to track students in a boarding school of their location at the selected restricted area.

As summary, based on the successful of RFID applications in various fields as discussed above, it shows that its application is endless. This section onwards explains the RFID application in tracking of laboratory equipments movement to ensure its availability. It also aims at helping the lab administrator in monitoring the equipment from lost or misplaced. The monitoring of equipments movement is not only being monitored by the lab administrator but also by the top management through online databases.

3. System architecture

Building an automated tracking applications by integrating web services guarantee many benefits, such as reduce clerical task and ease the management burden. The RFID-based Equipment Tracking System is an integrated system that offers an effective solution of managing items especially for large scale environment. It combines the RFID technology and security devices to ensure the items are always been monitored and secured. The system enable the university to give admission to selected individual to access locations, permit movement of items, record the important data and also enable the viewing of record via internet.

A faculty usually has a number of laboratories. Faculties with technical courses such as Information Technology and Engineering usually have more laboratories. To implement the system, an appropriate design is required to make sure it is suitable for the number of laboratories and equipments in all laboratories. In this study, the design of the system which utilizes RFID is divided into two; hardware design and software design as shown in the architecture diagram in Figure 1.

There are six important components involved as illustrated in Fig. 1, (1) RFID Tag, (2) RFID Reader, (3) Personal Computer, (4) RS232 Cable, and (5) LAN HUB and 6) CCTV Camera The master server contains the database which is used to store all data collected from RFID reader where user can read or change information in the database. The RFID tags contain antennas to enable the receiving and transferring data. The passive RFID tag creates power from magnetic field and use it to energize the circuits of the RFID chip and sends information back to the reader in the form of radio-frequency waves. The physical layer of the system is depicted in Figure 2. It shows how the computers and the master server are connected. The software involved in developing the system is also outlined.

In the system, RFID technology were implemented to enable data to be automatically recorded where each tag is embedded in the metric card (working pass) for individual and attached to each equipments. The lab administrator will grant an access to selected individual to enter a laboratory and also enable selected individual to move items out from the lab and within the organization. Upon the individual is found attempt to force the process the camera is triggered and activated to document the image of intended person and buzz the alarm system and notify the person-in-charge.



Fig. 1. System Architecture



Fig. 2. Physical layer of the system

4. Application scenarios

The developed prototype is an online laboratory monitoring system that has three purposes; which typically composed of (1) Laboratory grant access (2) Inventory control, and (3) Online data viewing. The prototype has been applied at the UTHM research project lab. To illustrate the concept, a sample of layout of application was provided in Figure 3.



Fig. 3. Application scenario layout

In the system, RFID tag is attached to both users and equipments. The RFID reader is located at each Laboratory to record and verify the RFID tags in the area. Each laboratory is equipped with a surveillance camera and an alarm indicator to deal with unforeseen circumstance events. The recorded data is stored and managed by a central computer whereby each laboratory computer is connected via intranet connection to ease any information received from computer lab can be easily transmitted to central computer. The main purpose of data, which is stored at the central computer, is to ease the management to have a look the whereabouts of equipment and record of in-out information. The administrator will grant the personal level access, equipment status and also permit online monitoring to authorize individual.

Legally attempt to enter a laboratory with authorize RFID identification (id), lead the magnetic door to unlock (door open) and record the entry information. Illegally attempt to access the laboratory, the door keep locked and activate the camera and warning sign is indicated to the system. Once the system detects a forceful behavior such as shaking the door, the system triggers an alarm to notify the security. In side of inventory control, intended user must be registered with authorized id before granted to move or lend the equipments, once verified, magnetic door will unlock and information is recorded. Otherwise, the registered id requires re-verification.

5. Implementation

As mentioned in previous section, the RFID-based Equipment Monitoring System is used to keep track the record on laboratory equipment. Hence, the laboratory, its equipments and users who use the equipment in the laboratory need to be part of the system entities. This can be done by enrolling these entities in the system.



Fig. 4. Access laboratories and equipments flowchart

At this moment, only three (3) laboratories have used the system and only authorised personnel are allowed to access the labs. In order to ensure only the authorised user login to the labs, they need to present their RFID card. Each laboratory is equipped with magnetic door. Therefore, the RFID card acts as a key to unlock the magnetic door. All equipments placed in the labs are tagged with RFID and registered in the system. This equipment can be used and borrowed by the user either in the same laboratory or in other laboratories. For the latter the user's RFID card and the equipment's tag should be readable by the RFID reader.

Once the information is successfully matched by the system, the magnetic door will be unlocked. Otherwise, the door remain locked if only the reader able to read equipment's information but not the user's information. Figure 4 illustrates the flow to access laboratories and equipments.



Fig. 5. The main GUI of RFID-based Equipment Tracking System



Fig. 6. The system flow of data management module

The system has two main purposes; first is to register user, equipment and laboratories to be part of the system entities. This is done by the system administrator through data management module. The second is to keep track the equipment and to monitor the activities of the user. The latter can be accessed through monitoring module. These two main purposes are presented in the form of graphical user interface as shown in Figure 5.

The data management module system flow is illustrated in figure 6. This module can only be accessed by authorised personnel to maintain the integrity of the data. Thus, system administrator needs to enter the correct password in login page as shown in Figure 7. Users are allowed to re-enter the password up to three (3) times for invalid password before the system activates the alarm system.

🙀 rEM User's Login		PrEM Administrator Login	
RFID-BASED EQUIPMENT MONITORING SYSTEM		RFID-BASED EQUIPMENT I SYSTEM	MONITORING
- USER LOGIN		USER L	E9
USER ID 01131		USER	•
PASSWORD	1	PASS NO RECOR	D 111
LOGIN NESET	CANCEL	LOGIN RESET	CANCEL
(a)		(b)	

Fig. 7. System administrator's (a) entering the password and (b) warning message for invalid access

🛢 rEM Data Manage	ment 🗖 🗖 🔀
Admin Logout	
Equipment	T UPDATE/DELETE VIEW REPORT
User	
On-Loan Equipment	JEL 002
EQUIPMENT ID :	0004883261
EQUIPMENT NAM	Dinital Multimeter
DESCRIPTION :	Use to measure electrical quantities such as voltage, current, resistance, frequency, tempreture,capacitance and time
	period
MODEL :	Fluke 179
	20
QUANTITY :	20
PREVIO	JS ADD NEXT CLEAR CANCEL

Fig. 8. Data Management Module



Fig. 9. Authorised user



Fig. 10. The system flow of data monitoring module

Then system administrator is able to view the data if the administrator is the authorized personnel. The data management module handles four (4) sub-modules which are described as Figure 8. According to Figure 8, *Equipment* sub module allows the system administrator to add new equipment and maintain the equipment record that is assigned in the laboratory. RFID tag is attached on the equipment to track down its status. *Lab* sub module allows the system administrator to enroll any laboratory to the system. *User* sub module allows the system administrator to enrol any user that wants to be in the system. After the user has been registered in the system, each will be given an RFID card. This card is used to authorise access the intended laboratory. The user needs to bring along the card to enter or to leave the laboratory. If user brings in/ out any equipment to/ from its registered laboratory, the card and the equipment's tag should be read by the RFID reader without fail in order to unlock the magnetic door. Figure 9 shows an example of successful login to laboratory.

On-loan equipment sub module allows the system administrator to register the status of equipment; whether it is in place or it is circulated around laboratory under an authorised user.

The system flow of monitoring module is shown in Figure 10. The module allows the administrator to monitor on-loan equipment, users' activity and their status. This module is designed so that it can be viewed by the administrator internally (intranet access) or remotely (internet access). Here, the discussion is focused on remote access. In order to use this module either internally or remotely, the administrator needs to log-in to the system as shown in Figure 11.



Fig. 11. The login page of system

rEH System - Healtin Firefox:							(F. 15	
e Dit gen regner Buildaria	Deer, Dre lies							
Calification C X 🕼 Interchantine alternation where the					+ - 30-			
Post Vistal 🗋 Geting Started 📥 Late	ent misdires 🙆 Curture	en Line 🗋 free total 🗋 way	toni Materiala 🚺 🕷	findows Hadas 🚺	Without			
0 - 10		81. E · E ·		12			117.5	
C (EM System	1.0							
MONITOR	ang ber ang	and the second second						
and the state of the state of the		Contractor and the second second second	-					
Address of the Address of the	and a formation of the second	and the second second						
FORP SHOVENERS BERACTIVITES	WSER STATUS				We	100 1 2011	20.00.10	
SPARCHING CRITFILLA	UNER 1D	NAME	EQUIP ID	START	END DATE	THE IN	TIME OUT	
(Diag the list far key terms)	009801	Model Arthur him Armai	0004881361	05.01.5011	19.41.2011	an 45 50	17 28 33	
Les Leves Lincetory in	61141	Zuranah binni Ahar	1002487295	16-01-2011	19-81-2011	14 25 38	16:00:13	
Ever III	81990	Formash hinti Alstand	0001101211	01-01-2011	19-01-3011	14:15:10	16.10.21	
Which Lab ?		Change of the	1	1.0.01.000	10.00.000			
INSTRUMENTATION LAS	* Click St	CTP ID to view equipment	a desails.					
Option continently								
C 1994								
🗢 Maals & Year 🛄								
O Specify Date Press Itel								
O Unspectied								
V	NEW 1							

Fig. 12. On-loan equipment page

CEM System - Marcilla Firefox							121日
de Ede geve Higtory Boolevarte	Tablesi Josh	1MP				-	
COLLEC X OL	Mp.(im.Net.	division and involution	this the				
the set of the set of the	and the state of the	(internetic	A first interest 17 working the latter		er (Nessen)		
				-	Contraction of the local division of the loc		- 115
0110	and the second	and the	and the second	and the second	16. C		- (V.0
EM System							
MONITO	ED8G	and the second second	Tooold -	_			
THE DO Alternative and she alter		and shares	the actualizes in 1219 Servers.				
ERAP MOVEMENT MAR ACTIVITY	ALL BREETA	195				Wed, Jan 5, 3	011 . 20 . 30 : 22
CONTRACTOR CONTRACTS	- 1		1	In the second second	-	1.000	
A CONTRACTOR CONTRACTOR OF	3	USER ID	NAME	DATE IN	11NE 19	DATE OUT	TIME OUT
Fregathe Ant for key commit	1	00001	Steller Arbin ben Arbin	05-01-2011	197.45:38	05-01-2011	10.00.11
Day Tangan Laboratory M	- P	83,000	Fathersh blast Alternal	41.41.5011	14.25.10	05.02.2011	16.40.11
Date: Mitt	2		All had been here been	01.41.3011	14.00.11	05.01.2011	17.05.04
		#1677	Hanida hinti Malian	05-01-2011	18-01-70	05.05.2011	17:00:02
NUCLEAR AND ADDRESS ADDRESS		66755	Alamad Zalci him Alamad Zalari	05-01-2011	15-02-22	05-02-2011	17.01.05
		01015	Alchhour Alb Alb Alchhourt	05-40-3011	15-04-01	04-01-2011	11 06 62
Partinen montriss under les		-		And an open statements		1	
O Telle							
🖸 Maark & Yese 🛄							
	2 M 1						
C Result Date Final Line							
C TRANSPORT							
	1						
	VIEW						
1	B						-
ore							

Fig. 13. Monitoring user's activity remotely

For successful login, the administrator is allowed to view and find a specific record on onloan equipment. Figure 12 shows on-loan equipment based on laboratory and specific date. As shown below, the following on-loan information is taken from instrumentation lab for Jan 5, 2011. The system is also designed so that the administrator could click on *Equip ID* to view equipment details borrowed by the user.

Figure 13 shows that the administrator is able to view user's activity at each laboratory. In the following example, it shows who has used the instrumentation lab on Jan 5, 2011. The user status tab contains information on which laboratory is allowed and the valid period as shown in Figure 14. By default, this page displays the status of all users. It also could display the status of certain user by selecting specific information, for instance *UserID* keyword to perform the searching process.

🕙 rEM System - Mozilla Firefox								×
Eile Edit View History Bookmarks Yahoo! Iools	Help							
🔇 💽 - 😋 🗙 🏡 🗋 http://rem.fkee.uthm.edu.my/monitor.php 🛛 🔶 - 🔽 - Yahoo							P	
🙍 Most Visited 🗋 Getting Started 🔊 Latest Headlines 📋 Customize Links 📄 Free Hotmail 🇋 Windows Marketplace 📄 Windows Media 📄 Windows								
Sol Seat	асн 🕂 🐌	🙆 🖬 • 🖂 • 🚄🕮 -	· 💷 💽 •	- 🛃 - 🌌 - 🛃			+ • @	
rEM System								-
HOME MONITORING	ABOUT	LOGC	UT					^
PM Dr. Ahmad, you are now allowed to monito	or and trac	k the activities in rEM Syst	em					
The bit Annual, you are now anowed to monite								
EQUIP MOVEMENT USER ACTIVITIES USER STAT	US				Wed,	Jan 5, 2011	, 20 : 30 :22	
SEARCHING CRITERIA :	STAFF ID	STAFF NAME	LAB ID	LAB NAME	START DATE	END DATE	STATUS	
(Drop the list for key terms)	00801	Mohd Azlan bin Azmi	JEP 003	COMMUNICATION	01-04-2010	01-01-2011	INACTIV	
Key Terms : User ID 🔗	00801	Mohd Azlan bin Azmi	JEP 003	COMMUNICATION	02-01-2011	02-01-2012	ACTIVE	
User ID: 00801	00801	Mohd Azlan bin Azmi	JER001	INSTRUMENTATION	12-02-2010	12-08-2011	ACTIVE	
WHICH Lab 7 NONE								
Option sort result by :								
 Today 								
🔿 Month & Year : 🛄								
• Specify Date From to								
● Unspecified ■								
VIEW								
×			_				~	~
Done	_						,	

Fig. 14. Viewing user's status

6. Conclusion

Laboratory equipment monitoring system using RFID is proposed to effectively monitor the in-out equipment from the laboratory. Via this system, every activity involving laboratory equipment can be monitored and updated through web based environment. For security purpose, only authorized personnel have the permit to monitor the transaction activities of laboratory equipment in real-time. The adaptation of RFID-based Equipment Monitoring System also would promote diversity on laboratory management which previously are handled manually.

7. References

- Ahmad Rafiq Adenan, Siti Zarina Mohd Muji, Mohd Helmy Abd Wahab. Automated Animal Tracking System using Radio Frequency Identification Tags. Proceeding of Computer Science and Mathematics Symposium 2006. KUSTEM, Kuala Terengganu, Terengganu, Malaysia, 8 – 9 November 2006
- EPC Global. RFID smart label practice experience. (2005-08-07) [2006-04-04], http://www.rfidi--nfo.com.cn/report/dissertation/20oS08/1655.html
- Haron, N. S., Saleem, N. S., Hassan, M. H., Ariffin, M. M. and Aziz, I. A. A RID-based Campus Context-Aware Notification System. Journal of Computing. Vol. 2. Issue 3.
- Herdawatie Abdul Kadir, Mohd Helmy Abd Wahab, Zarina Tukiran Mohd Razali Mohd Tomari and Mohd Norzali Hj. Mohd. (2010). Fusion of Radio Frequency Identification (RFID) and Fingerprint in Boarding School Monitoring System (BoSs), Sustainable Radio Frequency Identification Solutions, Cristina Turcu (Ed.), ISBN: 978-953-7619-74-9, InTech, Available from: http://www.intecheng.com/articles/abav//title/fusion.of radio frequency

http://www.intechopen.com/articles/show/title/fusion-of-radio-frequency-identification-rfid-and-fingerprint-in-boarding-school-monitoring-system-b

- Hsu, C-I, Shih, H-H, Wang, W-C. (2009). Applying RFID to Reduce Delay in Import Cargo Customs Clearance Process. Computers & Industrial Engineering. Vol. 57. pp. 506 – 519.
- Loebbecke, C. (2005). RFID Technology and Applications in Retail Supply Chain: The Early Metro Group Pilot. 18th Bled eConference on eIntegration in Action, June 6 – 8, 2005, Bled, Slovenia.
- Ngai, E. W. T. and Lo, S. Y. Y. (2008). Development of an RFID-based sushi management system: The case of a conveyor-belt sushi restaurant. International Journal of Production Economics, Vol. 112, Issue 2, pp. 630-645.
- Nor Suryani Bakery, Ayob Johari, Mohd Helmy Abd Wahab, Danial, Md. Nor. RFID Application in Farming Management System. In Proceeding of 3rd International Conference on Robotics, Vision, Information and Signal Processing 2007 (ROVISP2007), Penang, 28 – 30 November 2007
- Oztekin, A., Pajouh, F. M., Delen, D., and Swim, L. K. (2010). An RFID Network Design Methodology for Asset Tracking in Healthcare. Decision Support Systems. Vol. 49, pp. 100-109.
- Oztaysi, B., Baysan, S., and Akpinar, F. (2009). Radio Frequency Identify (RFID) in hospitality. Technovation. Vol. 29. Pp. 618-624.
- Robert, C. M. (2006). Radio Frequency Identification (RFID). Computers & Security, Vol. 25. Pp. 18 – 26.
- Tan, T-H, Chang, C-S. (2010). Development and Evaluation of an RFID-based e-Restaurant System for Customer Centric Service. Expert System with Applications. Vol. 37 Issue 9.
- Voulodimos, A. S., Patrizakis, C. Z., Sideridis, A. B., Ntafis, V. A., and Xylouri, E. M. (2010). A Complete Farm Management System based on Animal Identification using RFID Technology. Computers and Electronics in Agriculture. Vol. 70. Pp. 380 – 388.
- Yan, B. and Lee, D. (2009). Application of RFID in Cold Chain Temperature Monitoring System. 2009 ISECS International Colloqium on Computing, Communication, Control, and Management. Aug. 8-9, 2009. Sanya, China.

Zhang, X., Yue, S., and Wang, W. (2006). The Review of RFID Applications in Global Postal and Courier. The Journal of China Universities of Post and Telecommunications. Vol. 13. Issue. 4.



Designing and Deploying RFID Applications

Edited by Dr. Cristina Turcu

ISBN 978-953-307-265-4 Hard cover, 384 pages Publisher InTech Published online 15, June, 2011 Published in print edition June, 2011

Radio Frequency Identification (RFID), a method of remotely storing and receiving data using devices called RFID tags, brings many real business benefits to today world's organizations. Over the years, RFID research has resulted in many concrete achievements and also contributed to the creation of communities that bring scientists and engineers together with users. This book includes valuable research studies of the experienced scientists in the field of RFID, including most recent developments. The book offers new insights, solutions and ideas for the design of efficient RFID architectures and applications. While not pretending to be comprehensive, its wide coverage may be appropriate not only for RFID novices, but also for engineers, researchers, industry personnel, and all possible candidates to produce new and valuable results in RFID domain.

How to reference

In order to correctly reference this scholarly work, feel free to copy and paste the following:

Mohd Helmy Abd Wahab, Herdawatie Abdul Kadir, Zarina Tukiran, Noraisah Sudin, Mohd Hafizz Ab. Jalil and Ayob Johari (2011). RFID-Based Equipment Monitoring System, Designing and Deploying RFID Applications, Dr. Cristina Turcu (Ed.), ISBN: 978-953-307-265-4, InTech, Available from:

http://www.intechopen.com/books/designing-and-deploying-rfid-applications/mohd-helmy-abd-wahabherdawatie-abdul-kadir-zarina-tukiran-nor-aisah-sudin-mohd-hafiz-a-jalil-and-ay



InTech Europe

University Campus STeP Ri Slavka Krautzeka 83/A 51000 Rijeka, Croatia Phone: +385 (51) 770 447 Fax: +385 (51) 686 166 www.intechopen.com

InTech China

Unit 405, Office Block, Hotel Equatorial Shanghai No.65, Yan An Road (West), Shanghai, 200040, China 中国上海市延安西路65号上海国际贵都大饭店办公楼405单元 Phone: +86-21-62489820 Fax: +86-21-62489821 © 2011 The Author(s). Licensee IntechOpen. This chapter is distributed under the terms of the <u>Creative Commons Attribution-NonCommercial-ShareAlike-3.0 License</u>, which permits use, distribution and reproduction for non-commercial purposes, provided the original is properly cited and derivative works building on this content are distributed under the same license.